

LEMAS® SHEET METAL MACHINERY

FOOT SHEAR



LB-416F

SPECS MODELS	Capacity mm (in)	Back gauge range mm (in)	Front gauge range mm(in)	Shipping weight kg (lbs)	Size of case mm (in)
LB-316F	1.5×915 (16GA× 36")	650 (25-1/2")	610 (24")	440 (968)	1296×737×1270 (51"× 29"× 50")
LB-416F	1.5×1320 (16GA× 52")	650 (25-1/2")	610 (24")	530 (1166)	1677×991×1270 (66"× 39"× 50")
LB-416P	1.5×1320 (16GA× 52")	650 (25-1/2")	610 (24")	590 (1300)	1720×660×1190 (68"× 26"× 47")

SPECIAL FEATURES:

Strong on features, these shears offer precision shearing at its best. Simple to operate, ideal for shearing mild steel through 1.5m/m(16GA)as well as plastic,lead,zinc,aluminum,brass & copper etc.The pneumatic shear LB-416P is with the advantage of air operation for high speed precision operation. Heavy duty cylinders provide up to 40 strokes per minute and operate at a pressure of 65 PSI.

STANDARD EQUIPMENTS:

- Manual back gauge
- Front gauge & side gauge
- Pair of High Carbon High Chrome Steel blade
- Finger guard
- Protractor gauge