

Slip Rolls & Multiroll

Hand Slip Rolls



LF-322



3-ROLLS

Power Slip Rolls



LF-416E

MODEL	CAPACITY (mm)	ROLL DIAMETER (mm)	GEAR RATIO	SPEED (M/min.)	SHIPPING WEIGHT (kg)	SIZE OF CASE (mm)
LF-124	0.6 x 305	25	1:1	0.079	13	483 x 229 x 305
LF-126	0.5 x 460	25	1:1	0.079	14	635 x 229 x 305
LF-220	1.0 x 610	50	1:1	0.157	110	990 x 430 x 460
LF-322	0.8 x 910	50	1:1	0.157	130	1240 x 430 x 460
LF-416U	1.6 x 1270	75	5:1	0.048	260	1650 x 460 610

MODEL	CAPACITY (mm)	ROLL DIAMETER (mm)	MOTOR (hp)	SPEED (M/min.)	SHIPPING WEIGHT (kg)	SIZE OF CASE (mm)
LF-212E	2.5 X 670	75	2	3.3 5.3 8.3	280	1300 x 630 x 800
LF-314E	2.0 X 970	75	2	3.3 5.3 8.3	310	1600 x 630 x 800
LF-416E	1.5 X 1270	75	2	3.3 5.3 8.3	360	1900 x 630 x 800
LF-210E	3.0 X 670	90	3	3.9 6.3 9.9	370	1350 x 660 x 900
LF-312E	2.5 X 970	90	3	3.9 6.3 9.9	440	1650 x 660 x 900
LF-414E	2.0 X 1270	90	3	3.9 6.3 9.9	470	1950 x 660 x 900
LF-516E	1.5 X 1550	90	3	3.9 6.3 9.9	530	2250 x 660 x 900


Rotary Machine



LC-222L

STANDARD EQUIPMENTS:

- 2 pairs of bending rollers "V"
- 1 pair of flanging roller "BC"
- 1 pair of closing roller "ZA"
- 1 pair of joggling roller "F"
- 1 pair of crimping roller "E"
- 1 special wrench.




Power Multiroll



LC-2E

STANDARD EQUIPMENTS:

- 1 pair of swaging roller "S"
- 1 pair of joggling roller "F"
- 1 special wrench.
- Motor and controls 1/2HP



MODEL	CAPACITY (mm)	ROLLER CENTER (mm)	WORKING DEPTH (mm)	MOTOR (hp)	SPEED (M/min)	SHIPPING WEIGHT (kg)	SIZE OF CASE (mm)
LC-222L	0.8	50	178	X	X	32	460 x 410 x 155
LC-2E	1.25	50	305	1/2	2.3 4.2 6.9 13.9	90	715 x 460 x 1120

LEMAS®

LIEN HSIEN MACHINERY CORP.

63, Lin Sen East Rd., Chia-Yi, 600, Taiwan
 TEL:+886-5-272-1188 FAX:+886-5-272-1177
 TEL:+886-5-278-1777 FAX:+886-5-278-4120
 E-mail:lemas@lemas.com.tw
<http://www.lemas.com.tw>



LYNNTTEK INC.

Rm. 5A13, No 5, Hsin-Yi Rd, Sec.5, Taipei 110, Taiwan
 TEL:+886-2-2723-5808 FAX:+886-2-2723-5909
 E-mail:info@lynntek.com
<http://www.lynntek.com>